

| Ref # | Part Number Qty | Description |
|-------|-----------------|---|
| 1 | 34919A | Cylinder (Incl. 2,3 & 4) (2-5/8" Bore) |
| 2 | 27652 | Pin, Dowel |
| 3 | 27642 | Pipe plug, 1/4-18 |
| | 32630 | Seal, Oil |
| | 29536 | Blower Housing Baffle (Without electric starter knock |
| Ŭ | 2000 | out) (Use as required) |
| | | |
| 5 | 35256A | Blower Housing Baffle (With electric starter |
| | | knockout) (As req.)(point ign.) |
| 6 | 650561 | Screw, 1/4-20 x 5/8" |
| | 29538 | Base, Engine mounting |
| | 650542 | Screw, 5/16-18 x 3/4" |
| | 35252 | Crankshaft |
| | 29783 | Pin, Crankshaft gear (Used on early p rod.) |
| | 27884 | Gear, Crankshaft (Used on early production) This |
| 11 | 27004 | , |
| | | gear is serviceable ONLY when it is pinned to the |
| | | crankshaft. |
| 13 | 34531 | Piston, Pin & Ring Set (Std.) (2-5/8" Bore) |
| 13 | 34532 | Piston, Pin & Ring Set (.010" OS) |
| 13 | 34533 | Piston, Pin & Ring Set (.020" OS) |
| | 33312B | Piston & Pin Ass'y. (Std.)(2-5/8")(In cl.14) |
| | 33313B | Piston & Pin Ass'y. (.010" OS) (Incl. 14) |
| | 33314B | Piston & Pin Ass'y. (.020" OS) (Incl. 14) |
| | 27888 | Ring, Piston pin retaining |
| | 34854 | Ring Set (Std.) (2-5/8" Bore) |
| | 34855 | Ring Set (.010" OS) |
| | 34856 | Ring Set (.020" OS) |
| | 31295C | Rod Assy., Connecting (Incl. 17) |
| | 650662C | Bolt, Connecting rod (Incl. 2 pieces) |
| | 34034 | Lifter, Valve |
| | 33156 | Camshaft |
| | 30622A | Extension, Blower housing |
| | 650128 | Screw, 10-24 x 1/2" |
| | 650561 | Screw, 1/4-20 x 5/8" (Use as required) |
| | 30063 | Screw, 1/4-20 x 1/2" (Use as required) |
| | 30684 | Gasket Cylinder Cover |
| | 31451A | Cylinder Cover (Incl.26, 34, 127A, 12 9 & 130) |
| | 28460 | Seal, Oil |
| | 650488 | Screw, 1/4-20 x 1-1/4" |
| | 650493 | Screw, 1/4-20 x 1-3/4" |
| | 30699C | Rod Assy., Governor (Incl. 30 & 31) |
| | 30700 | Yoke, Governor |
| | 650494 | Screw, 6-40 x 5/16" |
| | 29642 | Ring, Retaining |
| | 31845 | Shaft, Mechanical governor |
| | 30588A | Spool, Governor |
| | 35479 | Washer, Flat |
| | 29193 | Ring, Retaining |
| | 30591 | Gear Assy., Governor |
| | 31843A | Bracket, Governor gear |
| | 650836 | Screw, 10-24 x 1/2" |
| | 32783 | Intake Valve (Std.) |
| | 32784 | Intake Valve (3/32" OS) |
| | 27878A | Exhaust Valve (Std.) |
| | 27880A | Exhaust Valve (3ld.) Exhaust Valve (1/32" OS) |
| 42 | ∠1 000A | Exhaust valve (1/02 00) |

Page 3 of 5

| | | Qty | Description |
|-----|---------|-----|---|
| 43 | 27882 | | Cap, Upper valve spring |
| 44 | 27881 | | Spring, valve |
| 45 | 32581 | | Cap, Lower valve spring |
| 47 | 650814 | | Screw, 10-24 x 1" |
| 49 | 32589 | | Key, Flywheel |
| | 28938C | | Gasket, Cylinder head |
| | 30938A | | Head, Cylinder |
| | 34251 | | Resistor Spark Plug (RJ-17LM) |
| | 610118 | | Cover, Spark plug (Use as required) |
| | 30939A | | Cover Assy., Cylinder head |
| | 650697A | | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| | 650694A | | Screw, 5/16-18 x 2" (Use as required) |
| | 650695A | | Screw, 5/16-18 x 2-1/4" (Use as required) |
| | 650691 | | Washer, Flat (Use as required) |
| | 650690 | | |
| | | | Washer, Belleville (Use as required) Locknut, 8-32 |
| | 30322 | | • |
| | 29916 | | Clamp, Governor lever (Use as require d) |
| | 32326A | | Lever, Governor |
| | 29918 | | Washer, Lock, No. 8 E.T. |
| | 30205 | | Bracket, Governor adjusting |
| | 650548 | | Screw, 8-32 x 5/16" |
| | 29216 | | Locknut, 10-32 |
| | 29826 | | Screw, 10-32 x 3/4" |
| | 32327 | | Link, Throttle |
| | 34661 | | Link, Governor |
| | 610973 | | Terminal Assy. (Use as required) |
| | 27896A | | Gasket, Valve chamber cover |
| | 28423 | | Breather Assy., Valve |
| | 28424 | | Element, Breather |
| 77 | 28425 | | Cover, Valve spring box |
| | 650128 | | Screw, 10-24 x 1/2" |
| | 35350 | | Tube Breather |
| 82 | 27915A | | * Gasket, Intake pipe to cylinder |
| 83 | 34712 | | Flange, Carburetor (Incl. 86A) |
| 84 | 30196 | | Screw, 5/16-18 x 3/4" |
| 85 | 31688A | | * Gasket, Carburetor |
| 86A | 650517 | | Screw, 1/4-20 x 13/16" |
| 87 | 27272A | | * Air Cleaner Gasket (Use as required) |
| 87 | 30767 | | Spacer, Cleaner (Use as required) |
| 94A | 34819 | | Elbow Assy., Air cleaner (Incl. 90,91,92,93,94,96) |
| | | | (Use in 730561 assembly only) |
| 404 | 24150 | | • |
| | 34158 | | Bracket, Fuel tank |
| | 650665 | | Screw, 1/4-14 x 7/8" |
| | 34159 | | Plate, Fuel tank mounting |
| 104 | 34186A | | Fuel Tank (Incl. 105 & 107) NOTE: These tanks |
| | | | were built with different size fuel inlet openings. |
| | | | Tanks with the 1-3/16" I.D. opening use fuel cap |
| | | | 33032 or 34210. Tanks with the 1-1/2" I.D. opening |
| | | | use fuel cap 35355. |
| 105 | 410144B | | Fuel Cap (White Plastic)(Std.)(As req uired) |
| | 33032 | | Fuel Cap (Red Plastic) (Spurt resistant, Low profile) |
| 100 | | | (Use as required) |
| | | | (000 00 10401100) |

| | Part Number 34210 | Qty | Description Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as required) |
|---|--|-----|---|
| 106 107 108 109 111C 111D 111E 115 116 117 118 119 120 121 122 123 124 127A 127 128 129 130 131 132 133 140 141 143A 143B 144 145 146 147 169 171 | 35355 29774 30962 26460 32158E 29747B 391026 33714 34390 32125 35009 650815 8116 29716 31691 28820 30727 31715 650152 31855 31793 31792 650778 650580 30845A 33450 30886A 30747 650890 33171 650578 33185 33700 33323 34011A 33590 33893A 32862 29574 730561 | | Fuel Cap (Red plastic) (Use as requir ed) Fuel Line (Braided, 8 1/4") (Use as required) Fuel Line (Braided, 32") (Use as required) Blower Housing (For electric starter) Screw, 5/16-24 x 21/32" Opt.Spark Arrest Muf.(Incl.143,143A,1 43B) Opt.Spark Arrest Muf.(Incl.112,143,14 4,144A) Deflector, Exhaust (Optional) Cup, Starter Screen, Starter cup Washer, Belleville Nut, Hex Screw, 1/4-28 x 7/16" Bracket, Air cleaner Screw, 10-32 x 1/2" Element, Air cleaner Screw, 8-32 x 3/8" Retainer, Bearing Bearing, Ball Washer, Thrust Washer, Lock Nut, Lock Bolt, Governor spring adjusting Nut, 10-32 Lock Spring, Extension Clip, Spark plug shorting Lockwasher, Shakeproof, 5/16 Screen, Muffler (Use as required) Screw, 8-18 x 3/8" (Use as required) Cover & tube, Muffler (Use as required) Cover & Tube, Muffler (Use as required) Dipstick (Incl. 146) "O" Ring Oil Fill Tube Nut, Conduit Elbow, 45-degree Air Cleaner Kit (Incl.74,79,80,87,88,89,90,91,92,94,95,96,97,99,100 & 230C) (Used only on engine with an externally vented fully adjustable carburetor) |
| 201 | 730164 | | Air Cleaner Ass'y. (Red Poly)(Incl.87,120,121,122,123,124 & 230)(As req.) |
| 201 | 730164 | | Air Cleaner Kit, Mini bike (Incl.87,120,121,122,123 & 124) (Use as required) |
| 209 210 | 730130 611084 650872 34443A | | Muffler Adapter Kit (Incl.110,112)(As req.) Flywheel Stud, Solid State mounting Solid State Assy. (Incl. 54) |

| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|---|
| 230 | 34346 | | Decal, Instruction |
| 230 | 550223 | | Decal, Name |
| 231 | 30547A | | Breaker Assy (Used on Std. Point igni tion) |
| 232A | 631021 | | Inlet, Needle Seat & Clip Assy. |
| 240 | 611077 | | Alternator (Optional) |
| 241 | 650868 | | Screw, 8-18 x 1-1/8" (3 required)(Opt .) |
| 242 | 611078 | | Connector, A.C. Lighting (Optional) |
| 242 | 611079 | | Connector, D.C. Charging (Optional) |
| 243 | 590610 | | Tube, Centering (Optional) |
| 244 | 590613 | | Alternator Shaft (Optional) |
| 250 | 632230 | | Carburetor (Incl. 85) (Refer to Division 5, Section A, Page 182 for breakdown) |
| 050 | 500,400,4 | | , |
| 252 | 590420A | | Rewind Starter (Refer to Division 5, Section C, page 25 for breakdown) |
| 254 | 33328D | | Starter Motor Kit (110-120 volt) This 110-120 volt starter motor kit may have been added to this engine. It can be added only if cylinder hasdrilled and tapped starter mounting bosses and a ring gear flywheel (see#255). Refer to service number stamped on end cap of motor or on decal for identificat |
| 255 | 30811A | | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter motor kits listed above) (Used on Std. point ignition before 1982) |
| 255 | 611042 | | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter motor kits listed above) (Used on Std. point ignition 1982 or later) |
| 255 | 611085 | | Flywheel (Minimum ring gear flywheel required on engines using 110-120 volt starter motor kits listed above) (Used on solid state external ignition) |
| 256 | 33235A | | Gasket Set (Incl. items marked*) |