

| | | Qty | Description (1) (2, 7 (2) P |
|-----|-----------------|-----|--|
| | 35123A | | Cylinder (Incl. 2, 3 & 4) (2-5/8" Bor e) |
| | 27652 | | Pin, Dowel |
| | 27642 | | Pipe plug, 1/4-18 |
| | 32630 | | Seal, Oil Player Hausing Poffle (Without electric starter knock |
| 5 | 29536 | | Blower Housing Baffle (Without electric starter knock out) (Use as required) |
| 5 | 35256A | | Blower Housing Baffle (With electric starter knockout) (As req.)(point ign.) |
| 6 | 650561 | | Screw, 1/4-20 x 5/8" |
| 7 | 29538 | | Base, Engine mounting |
| 8 | 650542 | | Screw, 5/16-18 x 3/4" |
| | 34876 | | Crankshaft |
| | 29783 | | Pin, Crankshaft gear (Used on early p rod.) |
| 11 | 27884 | | Gear, Crankshaft (Used on early production) This |
| | | | gear is serviceable ONLY when it is pinned to the crankshaft. |
| 13A | 33312B | | Piston & Pin Ass'y. (Std.)(2-5/8")(In cl.14) |
| | 33313B | | Piston & Pin Ass'y. (.010" OS) (Incl. 14) |
| 13A | 33314B | | Piston & Pin Ass'y. (.020" OS) (Incl. 14) |
| 13 | 34531 | | Piston, Pin & Ring Set (Std.) (2-5/8" Bore) |
| 13 | 34532 | | Piston, Pin & Ring Set (.010" OS) |
| 13 | 34533 | | Piston, Pin & Ring Set (.020" OS) |
| 14 | 27888 | | Ring, Piston pin retaining |
| | 34854 | | Ring Set (Std.) (2-5/8" Bore) |
| | 34855 | | Ring Set (.010" OS) |
| | 34856 | | Ring Set (.020" OS) |
| | 31295C | | Rod Assy., Connecting (Incl. 17) |
| | 650662C | | Bolt, Connecting rod (Incl. 2 pieces) |
| | 34034 | | Lifter, Valve |
| | 33156 30622A | | Camshaft Extension, Blower housing |
| | 650128 | | Screw, 10-24 x 1/2" |
| | 650561 | | Screw, 1/4-20 x 5/8" (Use as required) |
| | 30063 | | Screw, 1/4-20 x 1/2" (Use as required) |
| | 30684 | | Gasket Cylinder Cover |
| | 31303B | | Cover, Cylinder (Incl. 26 & 34) |
| | 31546 | | Bushing, Crankshaft |
| | 28427 | | Seal, Oil |
| 27 | 650488 | | Screw, 1/4-20 x 1-1/4" |
| 28 | 650493 | | Screw, 1/4-20 x 1-3/4" |
| | 30699C | | Rod Assy., Governor (Incl. 30 & 31) |
| | 30700 | | Yoke, Governor |
| | 650494 | | Screw, 6-40 x 5/16" |
| | 29642 | | Ring, Retaining |
| | 31845 | | Shaft, Mechanical governor |
| | 30588A | | Spool, Governor |
| | 35479 | | Washer, Flat |
| | 29193 30501 | | Ring, Retaining |
| | 30591 31843A | | Gear Assy., Governor Bracket, Governor gear |
| | 650836 | | Screw, 10-24 x 1/2" |
| | 32783 | | Intake Valve (Std.) |
| | 32784 | | Intake Valve (3/32" OS) |
| | 27878A | | Exhaust Valve (Std.) |
| 72 | 210101 | | Extradot varvo (ota.) |

| Ref # | Part Number C | ty Description |
|-------|---------------|--|
| | 27880A | Exhaust Valve (1/32" OS) |
| | 27882 | Cap, Upper valve spring |
| | 27881 | |
| | | Spring, valve |
| | 32581 | Cap, Lower valve spring |
| | 33876 | Gasket, Stator |
| 47 | 650489 | Screw, 1/4-20 x 5/8" |
| 49 | 32589 | Key, Flywheel |
| 51 | 28938C | Gasket, Cylinder head |
| 52 | 30938A | Head, Cylinder |
| | 34251 | Resistor Spark Plug (RJ-17LM) |
| | 610118 | Cover, Spark plug (Use as required) |
| | 30939A | Cover Assy., Cylinder head |
| | | |
| | 650690 | Washer, Belleville (Use as required) |
| | 650691 | Washer, Flat (Use as required) |
| | 650697A | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| 56 | 650694A | Screw, 5/16-18 x 2" (Use as required) |
| 56 | 650695A | Screw, 5/16-18 x 2-1/4" (Use as requi red) |
| 57A | 30322 | Locknut, 8-32 |
| 57 | 29916 | Clamp, Governor lever (Use as require d) |
| | 33454 | Lever Assy., Governor |
| | 29918 | Washer, Lock, No. 8 E.T. |
| | 650548 | Screw, 8-32 x 5/16" |
| | | · |
| | 29216 | Locknut, 10-32 |
| | 29826 | Screw, 10-32 x 3/4" |
| | 34661 | Link, Governor |
| | 34662 | Link, Throttle |
| 67A | 34677 | Control Bracket (Incl. 68, 69, 72 & 1 38) |
| 68 | 31342 | Spring, Compression |
| 69 | 650549 | Screw, 5-40 x 7/16" |
| 72 | 610973 | Terminal Assy. (Use as required) |
| | 27896A | Gasket, Valve chamber cover |
| | 28423 | Breather Assy., Valve |
| | 28424 | Element, Breather |
| | 28425 | Cover, Valve spring box |
| | 650128 | Screw, 10-24 x 1/2" |
| | | , |
| | 35350 | Tube, Breather |
| | 32446 | Grommet, Breather tube |
| | 27915A | * Gasket, Intake pipe to cylinder |
| | 34712 | Flange, Carburetor (Incl. 86A) |
| 84 | 30196 | Screw, 5/16-18 x 3/4" |
| 85 | 31688A | * Gasket, Carburetor |
| 86A | 650517 | Screw, 1/4-20 x 13/16" |
| 87 | 27272A | * Air Cleaner Gasket (Use as required) |
| | 30767 | Spacer, Cleaner (Use as required) |
| | 34783 | Filter, Pre-air |
| | 34782 | Filter, Air cleaner (Incl. 97) |
| | | , |
| | 34782 | Pop Rivet (1/8" dia.) (Purchase local ly) |
| | 34699 | Bracket, Air cleaner |
| | 34698A | Gasket, Air cleaner |
| | 30675 | Fitting, Breather |
| 94 | 34780 | Elbow, Air cleaner |
| 94A | 34819 | Elbow Assy., Air cleaner (Incl. 90,91,92,93,94,96) |
| | | (Use in 730561 assembly only) |
| | 050400 | |
| | 650163 | Screw, 10-32 x 7/8" |
| 96 | 650826 | Stud, 1/4-20 x 6.20, threaded both en ds |

| Pof # | Part Number | Otv | Description |
|--|---|-----|---|
| 97 99 100 101 102 | 650825 34781 650513 34158 650665 34186A | Qiy | Nut & Lockwasher, 1/4-20 Cover, Air cleaner Nut, Wing, 1/4-20 Bracket, Fuel tank Screw, 1/4-14 x 7/8" Fuel Tank (Incl. 105 & 107) NOTE: These tanks were built with different size fuel inlet openings. Tanks with the 1-3/16" I.D. opening use fuel cap 33032 or 34210. Tanks with the 1-1/2" I.D. opening use fuel cap 35355. |
| | 410144B 33032 | | Fuel Cap (White Plastic)(Std.)(As req uired) Fuel Cap (Red Plastic) (Spurt resistant, Low profile) (Use as required) |
| 105 | 34210 | | Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as required) |
| 106 107 108 109 110 111E 111 111D 111C 112 113 114 115 116 117 118 119 137 138 139 143 143B 143B 143A 144A 144 145 146A 167 168 | 35355 29774 30962 26460 32158E 29747B 27930A 34390 32401 33714 391026 30196 26073 650694A 32125 35009 650815 8116 29716 32410 34663 650821 650578 33185 33171 33323 33700 31297 29673 34174 650665 730561 | | Fuel Cap (Red plastic) (Use as required) Fuel Line (Braided, 8 1/4") (Use as r equired) Fuel Line (Braided, 32") (Use as required) Clamp, Fuel line (Use as required) Blower Housing (For electric starter) Screw, 5/16-24 x 21/32" * Gasket, Exhaust flange Deflector, Exhaust (Optional) Muffler Opt.Spark Arrest Muf.(Incl.112,143,14 4,144A) Opt.Spark Arrest Muf.(Incl.143,143A,1 43B) Screw, 5/16-18 x 3/4" Washer, Flat Screw, 5/16 - 18 x 2" Cup, Starter Screen, Starter cup Washer, Belleville Nut, Hex Screw, 1/4-28 x 7/16" Knob, Speed control Spring, Speed control Spring, Speed control Screw, 10-32 x 1/2" Screw, 8-18 x 3/8" (Use as required) Cover & tube, Muffler (Use as required) Screen, Muffler (Use as required) Screen, Muffler (Use as required) Cover & Tube, Muffler (Use as required) Dipstick (Incl. 146A) * Gasket, Oil fill Deflector, Exhaust Screw, 1/4-15 x 7/8" Air Cleaner Kit (Incl.74,79,80,87,88,89,90,91,92,94,95,96,97,99,100 & 230C) (Used only on engine with an externally vented fully adjustable carburetor) |
| | 730130 730164 | | Muffler Adapter Kit (Incl.110,112)(As req.) Air Cleaner Ass'y. (Red Poly)(Incl.87,120,121,122,123,124 & 230)(As req.) |

| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|--|
| 201 | 730164 | | Air Cleaner Kit, Mini bike (Incl.87,120,121,122,123 & |
| | | | 124) (Use as required) |
| 230A | 34686 | | Decal, Name |
| 230B | 34144 | | Decal, Control |
| 230C | 34704 | | Decal, Instruction |
| 230 | 34346 | | Decal, Instruction |
| 231 | 30547A | | Breaker Assy (Used on Std. Point igni tion) |
| 231A | 30548B | | Condenser |
| 232A | 631021 | | Inlet, Needle Seat & Clip Assy. |
| 240 | 611077 | | Alternator (Optional) |
| 241 | 650868 | | Screw, 8-18 x 1-1/8" (3 required)(Opt .) |
| 242 | 611078 | | Connector, A.C. Lighting (Optional) |
| 242 | 611079 | | Connector, D.C. Charging (Optional) |
| 243 | 590610 | | Tube, Centering (Optional) |
| 244 | 590613 | | Alternator Shaft (Optional) |
| 250 | 632257 | | Carburetor (Incl. 85) (Refer to Division 5, Section A, |
| | | | page 184 for breakdown) |
| 251 | 611038 | | Magneto NOTE: The complete magneto is not |
| 201 | 011030 | | available as an assembly. The magneto number is |
| | | | shown for reference purposes only. Order |
| | | | component parts individually, as shown in parts list. |
| | | | (Refer to Division 5, Section B, page 39 for |
| | | | breakdown) |
| 252 | 590420A | | , |
| 232 | 590420A | | Rewind Starter (Refer to Division 5, Section C, page 25 for breakdown) |
| | | | , |
| 254 | 33328D | | Starter Motor Kit (110-120 volt) This 110-120 volt |
| | | | starter motor kit may have been added to this engine. |
| | | | It can be added only if cylinder hasdrilled and tapped |
| | | | starter mounting bosses and a ring gear flywheel |
| | | | (see#255). Refer to service number stamped on end |
| | | | cap of motor or on decal for identificat |
| 255 | 30811A | | Flywheel (Ring gear flywheel requiredon engines |
| | | | using 110-120 volt starter motor kits listed above) |
| | | | (Used on Std. point ignition before 1982) |
| 255 | 611042 | | Flywheel (Ring gear flywheel requiredon engines |
| | | | using 110-120 volt starter motor kits listed above) |
| | | | (Used on Std. point ignition 1982 or later) |
| 255 | 611085 | | Flywheel (Minimum ring gear flywheel required on |
| 233 | 011000 | | engines using 110-120 volt starter motor kits listed |
| | | | above) (Used on solid state external ignition) |
| | | | , (|
| 256 | 33235A | | Gasket Set (Incl. items marked*) |
| | | | |